

LōDril® TR | LAD
DH | TRt



DH15 This member of our popular LōDril series can best be described in one word: versatile. Our engineers design each from the ground up to not only meet, but exceed the demanding specs of each job. Its low weight and slight frame make traversing the toughest terrain simple, and its low profile easily clears overhead obstructions. But don't underestimate the DH15's power because of its compact size. Its rotary torque reaches up to 15,000 ft-lbs, seamlessly punching holes up to 48 inches wide and 80 feet deep.



BAYSHORESYSTEMS.COM

sales@bayshoresystems.com | 844.644.3745



DH15

DH15 Specs

Rotary Torque (max) ¹	15,000 ft-lbs 20 kN-m
Kelly Winch Line Pull (first layer, max)	8,000 lbs 36 kN
Hole Diameter (max, recommended) ²	48 in 1,200 mm
Hole Diameter (min) ¹	18 in 450 mm
Drill Speed Range (LHS) ³	30/60/100 RPM
Crowd Stroke	24 in 600 mm 36 in 900 mm
Hole Depth (max) ⁴	80 ft 24 m
Attachment Height ⁴	9-21 ft 3-6 m
Excavator Weight Class (x 1,000) ⁵	16-35 lbs 7-15 kg
Square Kelly Bars Includes	Dewatering holes, locking pins & chains
Kelly Elements - Square (max)	7
Round Locking Kelly Bars Includes	Dewatering holes & retention chains
Kelly Elements - RLK (max)	5

1 - Running torque at low drill speed

2 - Dependent on ground conditions, tooling and operation

3 - Dependent on excavator

4 - DH Series configuration specific

5 - Excavator modifications may be required

DH SERIES Possibilities:

- Long-standing technology.
- Outstanding track record.
- Fastest bar set changes in the industry.
- The legacy continues...

The cornerstone of the LōDril® foundation.

BAYSHORESYSTEMS.COM

sales@bayshoresystems.com

844.644.3745