

LōDril[®] TR | LAD
DH | TRt



DH20 Amidst our impressive LōDril lineup, the DH20 is known as the pinnacle of performance, especially in traditionally challenging conditions. Need to drill on uneven terrain or slopes? Or beneath bridges and power lines? The DH20's compact size and enhanced mobility (attachment height ranges from 10-21 feet) will get you exactly where you need to be. Sporting a series of telescoping Kelly Bars and a more-than-capable rotary torque of 21,500 ft-lbs, this rig digs high-quality holes up to 48 inches in diameter and 80 ft deep.

**BAY SHORE**[®]
SYSTEMS, INC.

BAYSHORESYSTEMS.COM
sales@bayshoresystems.com | 844.644.3745



DH20

DH20 Specs

Rotary Torque (max) ¹	21,500 ft-lbs 30 kN-m
Kelly Winch Line Pull (first layer, max)	12,000 lbs 53 kN
Hole Diameter (max, recommended) ²	48 in 1,200 mm
Hole Diameter (min) ¹	18 in 450 mm
Drill Speed Range (LHS) ³	30/60/100 RPM
Crowd Stroke	24 in 600 mm 36 in 900 mm
Hole Depth (max) ⁴	80 ft 24 m
Attachment Height ⁴	10-21 ft 3-6 m
Excavator Weight Class (x 1,000) ⁵	35-50 lbs 15-25 kg
Square Kelly Bars Includes	Dewatering holes, locking pins & chains
Kelly Elements - Square (max)	7
Round Locking Kelly Bars Includes	Dewatering holes & retention chains
Kelly Elements - RLK (max)	5

1 - Running torque at low drill speed

2 - Dependent on ground conditions, tooling and operation

3 - Dependent on excavator

4 - DH Series configuration specific

5 - Excavator modifications may be required

DH SERIES Possibilities:

- Long-standing technology.
- Outstanding track record.
- Fastest bar set changes in the industry.
- The legacy continues...

The cornerstone of the LōDril® foundation.

BAYSHORESYSTEMS.COM

sales@bayshoresystems.com

844.644.3745